

Lead2passExam

> Contact Us Login / Register Search...

Lead2passExam

HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (1)

Pass Your Next Certification Exam Fast!

Everything you need to prepare, learn & pass your certification exam easily.
365 days free updates. First attempt guaranteed success.



Select a vendor...

Select an test...

Your email address

Free Download Demo

Top Certifications

- ▶ IBM Cognos ▶ Linux Essentials ▶ Magento Certified Developer Plus ▶ BCS Certification
- ▶ Citrix NetScaler ▶ Nokia Networks Certification ▶ Solutions Expert
- ▶ VCAP6-DCV Deployment ▶ Oracle Sales Cloud 2016 Certified ▶ Oracle Service Cloud
- ▶ CCP-N ▶ IBM Certified Mobile System Administrator ▶ Windows 7 ▶ APC Certification
- ▶ HPE Sales Certified

Top Vendors

- ▶ Logical Operations ▶ TIA ▶ Pegasystems ▶ IISFA ▶ Mile2 ▶ 3COM ▶ Altiris ▶ IIA
- ▶ AccessData ▶ Avaya ▶ BACB ▶ Nokia ▶ RAPS ▶ McAfee ▶ Professional Tests
- ▶ Mile2-Security ▶ CIPS ▶ Legato ▶ ASQ ▶ QlikView ▶ NSCA ▶ PSAT ▶ HRCI
- ▶ WorldatWork ▶ Guidance Software

What Client's Say

“ Passed the exam yesterday, but 10 questions new not came from this dump. every other questions are same. Totally valid. ”



Roy
★★★★★

“ This is still valid. Passed today with 80%. looked like 3-4 new questions. Many thanks! Good braindumps ”



Vic
★★★★★

<http://www.lead2passexam.com/>

Available Exam Cram and Valid Dumps - Lead2Pass Exam

Exam : **HPE6-A75**

Title : Aruba Certified Edge
Professional Exam

Vendor : HP

Version : DEMO

NO.1 An administrator deploys an AP at a branch office. The branch office has a private WAN circuit that provides connectivity to a corporate office controller. An Ethernet port on the AP is connected to a network storage device that contains sensitive information. The administrator is concerned about sending this traffic in clear-text across the private WAN circuit.

What can the administrator do to prevent this problem?

- A. Enable AP encryption for wired ports.
- B. Redirect the wired port traffic to an AP-to-controller GRE tunnel.
- C. Convert the campus AP into a RAP.
- D. Enable IPsec encryption on the AP's wired ports.

Answer: D

NO.2 Refer to the exhibit.

Summary	Enforcement	Rules
Enforcement:		
Name:	Enterprise Enforcement Policy	
Description:	Enforcement policies for local and remote employees	
Enforcement Type:	RADIUS	
Default Profile:	[Deny Access Profile]	
Rules:		
Rules Evaluation Algorithm:	Evaluate all	
Conditions	Actions	
1. (Tips:Posture EQUALS Healthy (0)) AND (Tips: Role MATCHES_ANY Remote Worker Role Engineer testqa) AND (Date:Day-of-Week NOT_BELONGS_TO Saturday, Sunday)	[RADIUS] EMPLOYEE_VLAN, [RADIUS] Remote Employee ACL	
2. (Tips:Role:EQUALS Senior_Mgmt) AND (Date:Day-of-Week NOT_BELONGS_TO Saturday, Sunday)	[RADIUS] EMPLOYEE_VLAN	
3. (Tips:Role EQUALS San Jose HR Local) AND (Tips:Posture EQUALS Healthy (0))	[RADIUS] WIRELESS_GUEST_NETWORK	
4. (Tips:Role EQUALS [Guest]) AND (Connection:SSID CONTAINS guest)	RestrictedACL	
5. (Tips:Role EQUALS Remote Worker) AND (Tips:Posture NOT_EQUALS Healthy (0))		

Based on the Enforcement Policy configuration, when a user with Role Engineer connects to the network and the posture token assigned is Unknown, which Enforcement Profile will be applied?

- A. RestrictedACL
- B. Deny Access Profile
- C. Remote Employee ACL
- D. EMPLOYEE_VLAN
- E. HR VLAN

Answer: B

Explanation:

Because posture token is unknown it doesn't match rule 1 even though he has the role engineer. It does not match any of the others due to the engineer role.

Hence, it will be assigned the default role of [DenyAccess]

NO.3 An administrator wants to implement bandwidth limits for guest users to restrict their Internet usage. On the Mobility Master (MM), where would the administrator define these limits?

- A. Firewall policy
- B. 802.1X policy
- C. User role
- D. AAA policy

Answer: A

NO.4 Refer to the exhibit.

```
Switch-1# show lin1-keepalive
```

```
Status and configuration - UniDirectional Link Detection (UDLD)
```

```
Keepalive Retries      : 4
Keepalive Interval    : 5000 ms
Keepalive Mode         : forward-then-verify
```

Port	Enabled	Physical Status	Keepalive Status	Adjacent Switch	UDLD VLAN
A23	Yes	up	failure	00fd45-653ae9	untagged

Switch-1 and Switch-2 connect on interface A23. The switches experience a connectivity issue. The network administrator sees that both switches show this interface as up. The administrator sees the output shown in the exhibit on Switch-1.

What is a typical issue that could cause this output?

- A. mismatched IP addresses on the VLAN for the link
- B. an issue with queuing, caused by mismatched QoS settings
- C. a hardware issue, such as a broken cable
- D. asymmetric routing introduced by a routing configuration error

Answer: C

NO.5 An administrator configures an ArubaOS-Switch for per-user tunneled node. Which protocols does the switch use to establish and maintain a connection with the Aruba Mobility Controller (MO)? (Select two.)

- A. GRE
- B. SSL
- C. IPSec
- D. PAPI

Answer: A,D

NO.6 What must an OSPF router do when it receives a link state update?

- A.** It must initiate a graceful restart timer.
- B.** It must run the shortest path first algorithm.
- C.** It must re-establish adjacency with its Designated Router and Backup DR.
- D.** It must participate in a new election for the Designated Router and Backup DR.

Answer: B